AD/A-002 982

COMPARATIVE MEASUREMENTS CF TOTAL
TEMPERATURE IN A SUPERSONIC TURBULENT
BOUNDARY LAYER USING A CONICAL EQUILIB-
RIUM AND COMBINED TEMPERATURE-PRESSURE
PROBE

Robert L. P. Voisinet, et al

Naval Ordnance Laboratory

NOL TECHNICAL REPORT

COMPARATIVE MEASUREMENTS OF TOTAL TEMPERATURE IN A
SUPERSONIC TURBULENT BOUNDARY LAYER USING A CONICAL
EQUILIBRIUM AND COMBINED TEMPERATURE-PRESSURE PROBE

BY
H.L.P. Voisinet
R.E. Lee
*H.U. Meier

NAVAL ORDNANCE LABORATORY
WHITE OAK, SILVER SPRING, MD. 20910

*DEUTSCHE FORSCHUNGS- UND VERSUCHSANSTALT FUR LUFT- UND
RAUMFAHRT E!V. AERODYNAMISCHE VERSUCHSANSTALT GOTTINGEN
(DFVLR-AVA), W. GERMANY

July 1974

AD A029982

NAVAL ORDNANCE LABORATORY
WHITE OAK, SILVER SPRING, MARYLAND 20910

AD/A002982

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS
BEFORE COMPLETING FORM

1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
NOLTR 74-10		

4. TITLE (and Subtitle)	5. TYPE OF REPORT & PERIOD COVERED
Comparative Measurements of Total Temperature In A Supersonic Turbulent Boundary Layer Using A Conical Equilibrium and Combined Temperature-Pressure Probe	
	6. PERFORMING ORG. REPORT NUMBER

7. AUTHOR(s)	8. CONTRACT OR GRANT NUMBER(s)
Robert L. P. Voisinet Roland E. Lee Hans-Ulrich Meier	

9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Naval Ordnance Laboratory Silver Spring, Maryland 20910 Code 313	AIRTASK A32320/292/69/ R009-02-030

11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
	July 1974
	13. NUMBER OF PAGES
	62

14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	15. SECURITY CLASS. (of this report)
	Unclassified
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Turbulent boundary layer, Temperature probe, Velocity profile, Temperature profile

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

The predominant probes used for measuring total temperature in a compressible boundary-layer flow are described. The results of a direct comparison between two of these probes, the conical equilibrium temperature probe (Danberg probe) and the combined temperature-pressure probe of the DFVLR-AVA, are presented. The comparison was made by testing the probes simultaneously

DD FORM 1473 1 JAN 73

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

20. Abstract (Continued)

in the nozzle-wall turbulent boundary-layer flow of the NOL
Boundary Layer Channel at zero and moderate heat-transfer
conditions. The measurements were made at a free-stream Mach
number of 4.9 and a Reynolds number per meter range between
1.84×10^6 and 2.57×10^7 at two axial locations in the uniform
flow regime of the nozzle. The results of the comparison
showed a good agreement between the two probes, with a maximum
difference in total temperature measurement of less than
± 2 percent over the range of application.

NOLTR 74-10   July 1974

COMPARATIVE MEASUREMENT OF TOTAL TEMPERATURE IN A SUPERSONIC
T'IRBULENT BOUNDARY LAYER USING A CONICAL EQUILIBRIUM AND
COMBINED PRESSURE-TEMPERATURE PROBE

This report documents results obtained in a comparative
experimental investigation of two probes used for the measure-
ment of total temperature in the supersonic turbulent boundary
layer.

ROBERT WILLIAMSON II
Captain, USN
Commander

Leon H. Schindel,

LEON H. SCHINDEL
By direction

CONTENTS

TABLES

FIGURES

APPENDICES

INTRODUCTION

Whereas the Mach number distribution in supersonic boundary layers can be obtained with sufficient accuracy from conventional Pitot probe measurements, the experimental determination of the total temperature requires a considerable effort in order to achieve high accuracy. Such reliable measurements are necessary to properly define the flow field in supersonic turbulent boundary layers.

The purpose of this paper is to report on the results of a direct comparison of two total-temperature measuring techniques. This is prefaced in the first part of the paper by a critical survey of existing total-temperature measuring instrumentation including the bare wire thermocouple probe, shielded stagnation temperature probe, mass flow probe, equilibrium temperature probe and combined temperature-pressure probe. The main advantages and disadvantages of these probes and their special application will be discussed. The second part of the paper describes the comparative probe measurements between the equilibrium temperature probe and the combined temperature-pressure probe.

SURVEY OF EXISTING MEASURING TECHNIQUES

Measurement Considerations

Conventional instruments for the probing of boundary-layer flows have been developed to measure either the total pressure, static pressure, total temperature or mass flow. In general, and for the range of application where perfect gas assumptions are valid, measurement of any three of the above four quantities

is sufficient to fully define a local flow field. These
quantities are measured either directly as in the measurement
of the total pressure behind a normal shock wave with a
Pitot probe, or indirectly as in the use of probes which
measure a local surface property which relates to one of the
above quantities through the use of basic perfect gas flow
relations. An example of the latter is the conical equilibrium
temperature probe which is used to infer the local stagnation
temperature from the measured cone recovery temperature and
Mach number.

In nearly all cases the total-temperature evaluation is
dependent upon the local Mach number. The Mach number is
generally obtained from the total pressure which is measured
with a Pitot probe. It is widely accepted that the accuracy
of the Pitot probe measurements are affected by three factors:
1. the distortion of the local flow streamlines about the
probe in the vicinity of the wall, 2. displacement effects
due to the integration of a nonuniform pressure distribution
over the probe open area which implies the center of pressure
is different from the probe geometric center, and 3. viscous
effects on the probe. These influencing factors on the Mach number
evaluation are present in almost all experimental measurements and
should be considered in the final analysis. These factors have
been extensively studied for Pitot probes (Refs. 1 to 4).

Intuitively, the same factors should also apply to other probing
devices. However, in the use of temperature probes the
influences of these factors have not been reported in as
much detail as with Pitot probes. The reasons are that
viscous effects are generally included in the probe calibrations
and, for most applications, temperature gradients in the

2

boundary-layer flow field are not as severe as the pressure gradients and do not warrant a displacement correction.

Presently there are four basic probe designs in use to measure the total temperature. These are the bare wire thermocouple probe, the shielded thermocouple probe, the conical-equilibrium temperature probe and the combined temperature-pressure probe. Each probe has its special design features and operational limitations.

Bare Wire Thermocouple Probe

The bare wire thermocouple probe generally refers to the configuration shown in Figure 1 taken from Reference 5. The probe configuration developed by Yanta is essentially a cylindrical wire aligned with its axis normal to the flow streamlines. This sensing wire is made of two small thermocouple wires welded together to form a thermocouple junction at the center. Consequently, the instrument senses the wire temperature at its center. The stagnation temperature is deduced from a heat-balance equation and empirical expressions for convective heat transfer to a cylinder in cross flow as derived in Reference 6. These computations include corrections for Mach number and viscous effects and wire support conduction losses. The application of bare wire probes to hypersonic flow further necessitates corrections for radiation. I. Beckwith et al. in Reference 4 and I. E. Vas in Reference 7 both considered heat losses due to radiation in addition to the conduction losses.

Due to the small dimensions of the bare wire probe, its application is ideally suited to boundary-layer investigations because measurements can be made very close to the wall. Because of the small mass of the wire, the probe also has a relatively fast response time in comparison to the other probes discussed herein.

3

The limitation of this probe relates to the aerodynamic loading of the wire at high Reynolds numbers. Early probe designs required large ratios of wire length to diameter to minimize conduction losses. A wire length to diameter ratio between 100 and 200 was generally used. This large ratio, together with the small wire diameter, usually resulted in a wire breakage due to high aerodynamic loading. Consequently, the probe was used only in relatively low dynamic-pressure flows. This large length-to-diameter ratio is no longer a stringent requirement in probe designs where wire support temperatures are monitored to provide an accurate correction for the end losses (See References 5 and 8). As an alternate means of overcoming the difficulties at the high dynamic pressures, H. D. Harris, Reference 9, used an arrangement proposed by W. S. Bradfield et al., Reference 10. In this arrangement, the thermocouple wires are mounted on the thin leading edge of a wedge-shaped probe-tip made of a heat-insulating material.

Shielded Stagnation Temperature Probe

The basic design of a shielded stagnation temperature probe is shown in Figure 2 as developed by E. M. Winkler, Reference 11, in 1954. The main advantages of this probe are that the thermocouple wire is protected by a shield against high dynamic pressure loads, and that the thermocouple is surrounded by subsonic flow. The subsonic flow in the probe is maintained by venting the air through a hole at the base of the probe where the probe entrance area is much larger than the vent-hole area. A sonic condition exists at the vent-holes on the condition that the ratio of Pitot to static pressure is over-critical. With a fixed vent-hole opening the mass flow inside of the probe varies with the free-stream Reynolds

4

number. This implies a change of the convective heat transfer
to the thermocouple junction and thus a change in the probe
recovery factor. For this reason, the probe must be calibrated
over the range of flow conditions to be investigated.

Further improvements of shielded thermocouple probes have
been made by many experimenters since the early work of
E. Winkler. R. E. Larson and A. R. Hansen, Reference 12,
reduced the size of such probes and P. J. Bontrager,
Reference 13, used a vented double shield to minimize
radiation losses at elevated temperatures.

Mass Flow Probe

Since the total temperature can be evaluated from the
measurements of static pressure, total pressure, and mass
flow, an indirect measurement of total temperature can be made
if a means is found of evaluating these quantities, in
particular, the mass flow. In 1953, D. Coles, Reference 1,
proposed a technique to measure the mass flow. If the flow
is supersonic, one may visualize a sharp-edged, tubular
probe with a sufficiently low internal pressure to permit
the existence of an attached shock system at the entrance
(See Figure 3). The probe inlet area then defines the
cross section area of the stream tube entrained by the probe.
D. Coles offered two methods to measure the mass-flow rate.
In the first method the probe is discharged into an evacuated
receiver for a measured time interval. The mass-flow rate
is calculated from the initial and final pressures and
temperatures in the receiver. This method was used
successfully by L. L. Liccini, Reference 14, in a hypersonic
boundary-layer flow. The major conclusions from Reference 14
were that the mass flow probe error increased as Reynolds
number was decreased and that a circular probe was more
satisfactory than a rectangular probe of the same height.

NOLTR 74-10

Figure 3 shows the second method of evaluating the mass flow
as applied by R. J. Stalker (Ref. 15). In this case a
calibrated sonic metering orifice, with a diameter larger than
the probe opening, is used between the probe and a vacuum pump.
Boundary layer measurements using the Stalker mass flow probe
were carried out by G. Hovstadius (Ref. 16). Practical
difficulties encountered with the application of this probe
appeared in the limited accuracy of the calibration procedure
used to get the effective probe entrance and the sonic nozzle
diameters.

In using a mass flow probe, the total temperature is
inferred from the two quantities: mass flux, ρu, and the Mach
number, M. Both quantities can be obtained from the same mass
flow probe. The mass flux can be determined from the mass-flow
rate measured and an effective probe entrance area. The Mach
number can be determined by disconnecting the vacuum system from
the probe and essentially using the probe as an impact pressure
indicator. This, together with a measured static pressure, permits
the calculation of the Mach number from the Pitot-Raleigh formula.

The primary condition for the probe to operate successfully
is that the flow must enter the probe undisturbed, i.e., the
stream tube captured by the probe must have the same cross-
sectional area as the probe entrance. In supersonic flow this
condition can be attained with a sharp leading-edge probe where
the oblique shock wave is attached to the leading edge. In
subsonic flow it is difficult to define the size of the stream
tube captured by the probe.

Combined Temperature-Pressure Probe

The combined temperature-pressure probe, see Figure 4, is
essentially a modified version of the shielded thermocouple probe
where the sonic vent-holes of the shielded thermocouple probe
are replaced by a mass-flow metering system. The modification
was based on the calibrations of shielded thermocouple probes

6

where it could be conclu'r'; that the dependency of the probe
recovery factor on Reyr s number could be related to the
mass flow through the probe. A detailed description of such
a probe, its calibration, and application for boundary layer
measurements is given in Reference 17.

In order to measure the mass flow through the probe, a
metering system is used whereby orifices of known area are
inserted between the probe and a vacuum pump. The mass flow,
and therewith the convective heat transfer to the thermocouple,
is controlled by the size of the metering orifice. The orifice
size is selected such that a sonic velocity is assured at the
orifice and the mass flow through the probe can he determined
from the orifice open area and the pressure and temperature
ahead of the orifice.

One limitation of this probe results from the relatively
long response time required to reach equilibrium conditions
when exhausting the probe through small orifices at low probe
pressures. Furthermore, in this low probe-pressure range
where the Reynolds number is correspondingly low, the relative
heat conduction through the probe thermocouple leads can become
large in relation to the low convective heat transfer to
the thermocouple and a calibration has to be established
for low mass flow rates. One advantage of the probe is that
it is particularly adaptable to measurements in complex flow
fields because both the Pitot pressure and stagnation temperature
can be measured consecutively at the same spacial location.

Conical Equilibrium Temperature Probe

The conical equilibrium temperature probe as developed by
J. E. Danberg, Reference 18, consists of a sharp, small
angled cone of low emissitivity, high conductivity metal
supported by a thermal insulator (See Figure 5). The cone
temperature, measured with a thermocouple imbedded in the
base of the cone, is assumed to be the recovery temperature

7

of the cone. Comprehensive calibration measurements endorse
a cone recovery factor calculation based on a laminar boundary
layer flow assumption, i.e., $r_p = (Pr)^{1/2}$ when radiation
losses are negligible. Based on this assumption, the total
temperature evaluation is reduced to a minimum since only
the cone temperature and Mach number need be evaluated.

The limitations of this probe arise from the difficulties
encountered in constructing probes of small diameter.
For this reason the probes cannot measure as close to the
surface in a boundary layer as, say, the bare wire probe.
Because of the relatively large mass of the cone, temperature
response is also relatively slow and such a probe is not
suitable in a short duration flow facility.

Table 1 summarizes the applications and limitations of
the various probes discussed. The chart should be useful
in determining a particular probe's usefulness and application.

COMPARATIVE PROBE MEASUREMENTS

Test Program

It has been an acceptable practice to demonstrate the
feasibility of a new probe design by comparing the results
of the new design against the results from an established
design in a well-defined flow field. Such was the case in
the conical equilibrium temperature probe - shielded thermo-
couple probe comparison, Reference 18, and in the fine-wire
stagnation temperature probe - conical equilibrium temperature
probe comparison, Reference 5.

The present report shows the results of a comparison between
the combined temperature-pressure probe and the conical
equilibrium temperature probe. The comparison was made in

the Naval Ordnance Laboratory Boundary Layer Channel on
the nozzle wall turbulent boundary layer flow at Mach number
4.9 for zero and moderate wall heat-transfer conditions.

Test Facility

The experiments were performed in the NOL Boundary Layer
Channel, Reference 19, shown in Figure 6. The supersonic
half-nozzle has for one wall a flat copper test plate, 2690 mm
long, along which the boundary layer measurements were made.
The opposite wall consists of an adjustable flexible plate
which was contoured to produce a Mach 4.9 zero-pressure-gradient
flow over the flat test plate beginning at 1397 mm downstream
of the nozzle throat. The comparative boundary-layer stagnation
temperature surveys were made at two locations along the
test plate, corresponding to 1700 and 2060 mm downstream of
the nozzle throat. The facility was operated at supply
pressures of 1, 5, and 10 atmospheres and at a supply
temperature of 340°K for the adiabatic wall runs and 420°K
for the moderate heat-transfer runs. The wall temperature
downstream of the nozzle throat region was held constant
through the test runs by cooling the copper test plate with
water. The test conditions are outlined in Table 2. Since
the experimental arrangement and test procedures used in
this study were similar to previous boundary-layer investigations
in this facility, Reference 2 should be consulted for further
information concerning the facility, test procedure, and
boundary-layer characteristics.

Instrumentation

The boundary-layer profile surveys were made by simul-
taneously traversing the combined temperature-pressure probe
and the conical equilibrium temperature probe through the
boundary layer in a double-probe support configuration as
shown in Figure 7. Each traverse was made from the free
stream towards the plate with a maximum movement of 11
centimeters. Data were recorded with the probes at rest and
only when the probe pressures and temperatures were
observed to have reached equilibrium conditions. The local
Pitot pressure was measured with the combined temperature-
pressure probe. The local total temperature through the
boundary layer was measured with both the combined temperature-
pressure probe and the conical equilibrium temperature
probe. Since the temperature probes were not of the same
diameter nor mounted exactly at the same distance from
the wall, the cone probe temperature data were interpolated
to the location of the combined temperature-pressure probe.
This allowed for the computation of all boundary-layer
parameters at the same y location.

Data Reduction

The local Mach number was calculated from the measured
Pitot pressure using the Rayleigh-Pitot formula or
Bernoulli's equation depending on the Mach number range.
The computations were based on the assumption of uniform
static pressure through the boundary layer with the static
pressure equal to the wall pressure.

The local stagnation temperature through the boundary layer was calculated from the following equation:

$$T_t = \frac{T_p}{r_p + \left(\dfrac{1 - r_p}{1 + \frac{\gamma-1}{2} M_p^2}\right)} \tag{1}$$

where T_p is the measured probe thermocouple temperature, r_p is the probe recovery factor, and M_p is the probe reference Mach number. For the conical equilibrium temperature probe the recovery factor was equal to $Pr^{1/2}$ assuming laminar flow over the probe tip. The probe reference Mach number was assumed equal to the cone Mach number as determined from cone flow equations. For the combined temperature-pressure probe, the probe reference Mach number was equal to the local Mach number and the probe recovery factor was obtained from a calibration of r_p versus the mass flux through the probe. This calibration was obtained with the probe in the free stream for a limited range of probe mass flux conditions. The calibration is discussed in the next section. The local recovery factor of the combined temperature-pressure probe was computed for each location in the boundary layer from the measured mass flow rate at that location. Finally, the local static temperature, T, was obtained from the measured total temperature and Mach number using the isentropic relation

$$T = \frac{T_t}{1 + \frac{\gamma-1}{2} M^2} \tag{2}$$

Combined Temperature-Pressure Probe Recovery Factor Calibration

Using the experimental arrangement shown in Figures 4 and 7, the calibration of the combined temperature-pressure probe was made with the probe located in the free-stream flow of the Boundary Layer Channel. The free-stream stagnation temperature was assumed equal to the tunnel supply temperature and a correlation of the probe temperature and stagnation temperature was evaluated in terms of the probe recovery factor, r_p, in the form:

$$r_p = \frac{T_p - T_\infty}{T_o - T_\infty} \tag{3}$$

where T_p is the measured probe temperature, T_o, the tunnel supply temperature, and T_∞, the freestream static temperature.

The mass flux through the probe was evaluated for each point in the calibration by exhausting the flow in the probe through sonic orifices. Because of this sonic condition at the orifice, the mass flux could be calculated from the measured pressure and temperature immediately ahead of the orifice, P_3 and T_3, and the effective diameter of the orifice, d_A, from the relation:

$$\dot{m} = \left(\frac{2}{\gamma-1}\right)^{\frac{1}{\gamma-1}} \left(\frac{\gamma}{\gamma+1}\right)^{.5} \quad \frac{\pi}{4} d_A^2 \, P_3 \left(\frac{2}{RT_3}\right)^{.5} \tag{4}$$

or, for $\gamma = 1.4$,

$$\dot{m} = 0.537 \, d_A^2 \, P_3 \left(\frac{1}{RT_3}\right)^{.5} \tag{5}$$

Recovery factor measurements were made for a range of mass
flux conditions by passing the probe exhaust through orifices
of differing diameter. A range of mass flow rates from 2×10^{-7}
to 7×10^{-6} kg./sec. was attained by exhausting through
orifices with geometric diameters of 0.155, 0.190, 0.246,
0.272, and 0.325 mm. Values of the geometric orifice
diameter were used in this data reduction. In Reference
20, the effective nozzle diameters were evaluated and
used in a similar date reduction procedure. This refinement
had reduced the scatter in the calibration data.

The recovery factor calibration was obtained for a
constant free-stream Mach number of 4.9 over a range of
free-stream Reynolds number conditions. The tunnel supply
pressure ranged from 1 to 10 atmospheres and the supply
temperature was 340°K and 420°K. The results of the probe
recovery factor calibration are shown in Figure 8, together
with a least square polynomial curve fit of the data in
the form

$$r_p = \sum_{i=1}^{5} a_i \, (e^{-\alpha \dot{m}})^{(i-1)} \tag{6}$$

Where: $\alpha = 0.32240 \times 10^6$

$a_1 = 0.981030$

$a_2 = 0.062327$

$a_3 = -0.185030$

$a_4 = 0.217070$

$a_5 = -0.186120$

Results of the Comparative Probe Measurements

The data described in the text of this report are
documented in the tables of Appendix B. The nomenclature
used in this computerized tabular output is defined in
Appendix A.

Several considerations are worth commenting on at
this time concerning the data documentation. First, the
free-stream stagnation temperatures measured with the conical
equilibrium and the combined temperature-pressure probe are
seen to differ slightly for any particular test run. The
main reason for this difference relates to the variation of
the tunnel supply temperature between the time the two
temperature measurements are made, i.e., the conical
equilibrium probe temperature is measured at the time the
Pitot pressure is measured while the combined temperature-
pressure probe temperature is measured at a slightly later
time when the probe is being vented. Because of possible variation
in the tunnel supply temperature and the time lag between subsequent
temperature probe measurements, the local stagnation temperature
through the boundary layer was non-dimensionalized to the
simultaneous free-stream stagnation temperature. All comparisons
of temperature data are made in terms of the stagnation
temperature ratio rather than the absolute temperature.
It can be noted that for y distances of less than 0.75 mm,
no temperature data are presented for the conical equilibrium
temperature probe because of the larger probe size and its
inability to measure as close to the wall as the combined
temperature-pressure probe. And finally, it must be pointed
out that no viscous flow or probe wall interference
corrections are made to the Pitot pressure data. These

effects are present. However, their influence is restricted
to low Reynolds number data and data very close to the wall.
Because these regimes are associated with the low Mach number
data for these tests the effect on the temperature evaluation
is minimal as can be deduced from equation (1) as M approaches 0.

Comparisons of the measured stagnation temperature profiles
obtained with the conical equilibrium temperature probe and
the combined temperature-pressure probe are presented in
Figures 9 to 12 for the two stations and two heat-transfer
conditions. Agreement in stagnation temperature between the two
probing techniques is good with a maximum deviation in
stagnation temperature measurement of the order of 2 percent.
The percent deviation in temperature measurement are
shown in Figure 13 as a function of distance from the
wall. The amount of data scatter in terms of temperature
deviation appears to be equal between the data with and without
heat transfer. However, the deviations appear to be greatest
in the inner portion of the boundary layer where the Reynolds
number is low. Under these conditions, the application of both
probing techniques needs further qualification. It should be
noted that the data reduction precedure used in Reference 20
led to smaller differences (± 1 percent) between the two temperature
measurements.

In proximity to the wall where the velocity and temperature
gradients are the strongest, both probes exhibit averaging
or displacement effects. Viscous interaction effects, as
previously discussed, are predominant in this low Reynolds
number regime. The conical equilibrium temperature probe data
in the vicinity of the wall could be influenced by the
interaction and possible reflection of the cone shock
wave with the wall. The combined temperature-pressure

15

probe data need further examination because the exhausted mass
flow rates through the probe were very low at the low
Reynolds number conditions. Figure 14 shows the range
of mass flow rates experienced in the boundary layer
profiles presented in this report. It is observed that
for the low Reynolds number tests (P_o = 1 atm.), the
probe recovery factor had to be de   mined almost exclusively
from the extrapolated portion of the curve fit. At these
low probe mass flow rates, it is questionable whether the
probe recovery factor is a function of the exhausted mass
flux alone. By plotting the percent deviation in total
temperature as a function of the exhausted mass flux through
the combined temperature-pressure probe (See Figure 15), it
can be seen that the percent deviation in total temperature
measurement becomes larger with decreasing mass flux. It is
still uncertain whether this trend is due to conduction losses
on the temperature-pressure probe thermocouple or due to any
one of the other previously mentioned effects on the cone
probe temperature.

CONCLUSIONS

Probes used to measure stagnation temperature distributions
in supersonic and hypersonic turbulent boundary layers are
discussed. Limitations and applications of each probe are
indicated.

Comparative probe measurements with the conical equilibrium
temperature probe and the combined temperature-pressure probe
lead to the following results:

The average differences between the measured stagnation temperatures in the Mach 5 supersonic turbulent boundary layers with and without heat transfer were in the range of $\pm$ 1.0 percent. At very low Reynolds numbers close to the surface the deviations increased to about 2 percent.

The conical equilibrium temperature probe is distinguished by its simple calibration, where the recovery factor can be assumed constant ($r_p = (Pr)^{1/2}$). Due to the relatively large probe size, measurements could not be obtained very close to the wall.

The combined temperature-pressure probe enables one to measure at one position of the probe the local stagnation temperature and total pressure. This can be important if complex flow fields are to be studied. Due to its smaller diameter, measurements closer to the surface could be made.

Although these investigations yielded a good agreement, further work should be undertaken to better classify and define the apparent discrepancies at low Reynolds numbers and in the vicinity very close to the wall.

17

REFERENCES

1. Coles, D., "Measurement in the Boundary Layer on a Smooth Flat Plate in Supersonic Flow," Part II, JPL Report No. 20-70, June 1953

2. Voisinet, R. L. P., Lee, R. E., "Measurements of a Mach 4.9 Zero-Pressure-Gradient Turbulent Boundary Layer with Heat Transfer, Part 1 – Data Compilation," NOLTR 72-232, 1972

3. Allen, J. M., "Pitot-Probe Displacement in a Supersonic Turbulent Boundary Layer," NASA TN D6759, April 1973

4. Beckwith, I. E., William, D. H., and Clark, F. L., "Comparisons of Turbulent Boundary-Layer Measurements at Mach Number 19.5 with Theory and an Assessment of Probe Errors," NASA TN D6192, June 1971

5. Yanta, W. J., "A Fine-Wire Stagnation Temperature Probe," NOLTR 70-81, 1970

6. Scrandon, M. D., Warshawsky, I., "Experimental Determination of Time Constants and Nusselt Numbers for Bare-Wire Thermocouples in High-Velocity Air Streams and Analytic Approximation of Conduction and Radiation Errors," NACA TN 2599, January 1952

7. Vas, I. E., "Flowfield Measurements Using a Total Temperature Probe at Hypersonic Speeds," AIAA Journal, Vol. 10, No. 3, pp. 317-323, March 1972

8. Behrens, W., "Total Temperature Thermocouple Probe Based on Recovery Temperature of Circular Cylinders," Int. J. Heat Mass Transfer, Vol. 14, pp. 1621-1630, 1971

9. Harris, H. D., "An Investigation of Turbulent Boundary Layer Characteristics with Particular Reference to the Effect of Heat Transfer and Pressure Gradient," Ph.D. Thesis, London University, 1970

10. Bradfield, W. S., Hanson, A. R., Sheppard, J. J., "Design, Calibration and Application of a Miniature Total-Temperature Probe," Trans. ASME, Ser. C., J. Heat Transfer, pp. 462-463, 1964

11. Winkler, E. M. "Stagnation Temperature Probes for Use at High Supersonic Speeds and Elevated Temperatures," NAVORD Report 3834, October 1954

12. Larson, R. E., Hanson, A. R., "Study of Subminiature Total Temperature Probes," NASA Report 2980, 1966

13. Bontrager, R. J., "Development of Thermocouple-Type Total Temperature Probe in the Hypersonic Flow Regime," AEDC-TR-69-25, 1969

14. Liccini, L. L., "NOL Hypersonic Tunnel No. 4 Results VII: Development and Calibration of Mass Flow Probes in Hypersonic Flow," NAVORD Report 4078, November 1955

15. Stalker, R. J., "The Use of Mass Flow Probe for Measurement of Hypersonic Boundary Layer Properties," FFA Report AU-624, Part 1, 1970

16. Hovstadius, G., "Measurement of Boundary Layer Properties in Two Hypersonic Nozzles," FFA Report AU-624, Part 2, 1971

17. Meier, H. U., "A Combined Temperature and Pressure Probe for Compressible Flow," AIAA Journal, Vol. 7, No. 3, pp. 529-530, 1969

18. Danberg, J. E., "The Equilibrium Temperature Probe, A Device for Measuring Temperatures in Hypersonic Boundary Layers," NOLTR 61-2, December 1961

19. Lee, R. E., Yanta, W. J., and Carner, J. W., "The NOL Boundary Layer Channel," NOLTR 66-185, November 1966

20. Meier, H. U., Lee, R. E., and Voisinet, R. L. P., "Total Temperature Probes for the Investigation of Turbulent Boundary Layers at Supersonic Speeds," 5th International Congress on Instrumentation in Aerospace Simulation Facilities, ICIASF 73 Record, IEEE Publication No. 73 CHO 784-9 AED, 1973

LIST OF SYMBOLS

d_A sonic metering orifice diameter

d_E probe entrance diameter

$\dot{m}$ mass flux through probe

M Mach number

M_p probe reference Mach number

P pressure

Pr Prandtl number (for air, 0.72)

P_s static pressure

P_{t2} Pitot pressure

r boundary layer recovery factor

r_p probe recovery factor, $\dfrac{T_p - T}{T_t - T}$

R gas constant

Re Reynolds number per meter, $\dfrac{\rho_\infty u_\infty}{\mu_\infty}$

T temperature

u velocity

x streamwise distance from nozzle throat

y distance normal to test plate surface

Subscripts

aw adiabatic-wall conditions

o tunnel supply conditions

p probe conditions

t stagnation conditions

Subscripts (Cont.)

w   wall conditions

3   conditions immediately ahead of sonic
                metering orifice

∞   free-stream conditions

Abbreviations

CE   conical equilibrium probe

CTP   combined temperature-pressure probe

TABLE 1 - COMPARISON OF TOTAL TEMPERATURE PROBES

Probe Type Ratings in Terms Of:	Fine Wire	Shielded	Mass Flow	Combined Temperature- Pressure	Conical Equilibrium
Measured Quantities	T_t	T_t	$\rho u, P_{t2}$	T_t, P_{t2}	T_t
Small probe size	G	F	F	F	(P)
Resistance to high dynamic loading	(F)	G	G	G	F
Response time	G	(P)	(P)	(P)	F
Ease of calibration	F	P	F	F	G
Low Reynolds number application	G	P	P	P	G
Application to subsonic flow	G	G	-	G	G
Application to hypersonic flow	G	G	-	-	G

G - Good
F - Fair
P - Poor
( ) - Improvement possible with further development
- - Unproved but possible

TABLE 2 - RUN NUMBERS AND TEST CONDITIONS

Run No.	Station (Meters)	P_o (Atms)	T_o (°K)	T_w/T_{aw}
108051	1.702	10.	340.	1.0
108052		5.		
108053		1.		
108104	2.057	5.		
108105		1.		
108091	1.702	10.	420.	0.8
108054		5.		
108055		1.		
108101	2.057	10.		
108102		5.		
108103		1.		

CERAMIC INSULATOR

0.50 ALUMEL

STAINLESS TUBING

0.025 ALUMEL

3.175 STAINLESS TUBING   BRASS   1.27 O. D. - 0.89 I. D.

BUTT WELD

0.025 CHROMEL

0.50 CHROMEL

THERMOCOUPLE LEADS

0.127 IRON-CONSTANTAN THERMOCOUPLE

TOP VIEW

SCALE

25.4 mm

THERMOCOUPLE LEADS

10°

0.127 IRON-CONSTANTAN THERMOCOUPLE

SIDE VIEW

FIG. 1 SCHEMATIC OF FINE-WIRE PROBE (5)

FIG. 2 SHIELDED THERMOCOUPLE PROBE (11)

FIG. 3 MASS FLOW PROBE (15)

FIG. 4 COMBINED TEMPERATURE-PRESSURE PROBE (17)

FIG. 5 DANBERG CONICAL EQUILIBRIUM TEMPERATURE PROBE (18)

PROBE HOLDER

CERAMIC INSULATOR

THERMOCOUPLE JUNCTION

25.4mm

1.27mm

7.29mm

TIP MATERIAL PLATINUM

10°

FIG. 6 NOL BOUNDARY LAYER CHANNEL

FIG. 7 ARRANGEMENT OF PROBES

○ CALIBRATION DATA USING
GEOMETRIC ORIFICE DIAMETERS
TO EVALUATE ṁ
M = 4.9

EQN. 6

ṁ X 10^6 (Kg/sec)

FIG. 8 RECOVERY FACTOR CALIBRATION CURVE FOR THE COMBINED TEMPERATURE-PRESSURE PROBE

FIG. 9 COMPARATIVE TOTAL TEMPERATURE MEASUREMENTS, $X=1.702$, $T_w/T_{aw}=1.0$

FIG. 10 COMPARATIVE TOTAL TEMPERATURE MEASUREMENTS X = 2.057, T_w/T_{aw} = 1.0

FIG. 11 COMPARATIVE TOTAL TEMPERATURE MEASUREMENTS, $X = 1.702$, $T_w/T_{aw} = 0.8$

FIG. 12 COMPARATIVE TOTAL TEMPERATURE MEASUREMENTS
X = 2.057, $T_w/T_{aw} = 0.8$

34

FIG. 3 PERCENTAGE DEVIATION OF THE COMPARATIVE TOTAL TEMPERATURE MEASUREMENTS

FIG. 14 RANGE OF APPLICATION OF THE COMBINED TEMPERATURE-PRESSURE PROBE RECOVERY FACTOR CALIBRATION

FIG. 15 PERCENTAGE DEVIATION IN COMPARATIVE TOTAL TEMPERATURE MEASUREMENTS AS A FUNCTION OF EXHAUSTED MASS FLUX

APPENDIX A

COMPUTER NOMENCLATURE

The nomenclature used in the computerized tabular output is defined as follows:

D	$= \rho$	= density
DE	$= \rho_\infty$	= free-stream density
DEL	$= \delta$	= boundary layer thickness
DSTR	$= \delta^*$	= displacement thickness
M	$= M$	= local Mach number
ME	$= M_\infty$	= free-stream Mach number
PO	$= P_O$	= tunnel supply pressure
PS	$= P_s$	= local static pressure
PSW	$= P_{sw}$	= local wall static pressure
RE	$= \dfrac{\rho_\infty u_\infty}{\mu_\infty}$	= free-stream Reynolds number per meter
STA	$= x$	= axial station
T	$= T$	= static temperature
TE	$= T_\infty$	= free-stream static temperature
TW	$= T_w$	= wall temperature
TT	$= T_t$	= stagnation temperature
TTE	$= T_{t_\infty}$	= free-stream stagnation temperature
TO	$= T_O$	= tunnel supply temperature
TH	$= \theta$	= momentum thickness
THE	$= \theta_E$	= energy thickness
THH	$= \theta_H$	= enthalpy thickness

U	= u	= velocity
UE	= u_∞	= free-stream velocity
X	= x	= axial distance in flow direction measured from nozzle throat
Y	= y	= distance normal to flat plate surface

The units used in the computerized tabular output conform to the International Standard of Units (Ref. A-1) and are defined as:

ATM	= atmospheres
CM	= centimeters
DEG.K	= degrees Kelvin
KG/M3	= kilograms per meter cubed
M	= meters
M/S	= meters per second
N/M2	- newtons per meter squared

Two symbols are used in the profile data listing and are defined as:

*	= denotes boundary-layer thickness, δ, where $u/u_\infty = 0.995$
**	= denotes free-stream location

Reference

A-1 Mechtly, E. A., "The International System of Units." NASA SP-7012

APPENDIX B
TABULAR DATA

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108051   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 1.702E+00   ME = 4.788E+00   DEL = 4.735E+00 CM
PO = 1.030E+06 N/M2   DE = 1.379F-01 KG/M3   DSTR = 1.751E+00 CM
TO = 3.381E+02 DEG.K   TE = 6.053E+01 DFG.K   TH = 1.743F-01 CM
PSW = 2.363E+03 N/M2   UE = 7.468E+02 M/S   THE = 3.177E-01 CM
TW = 2.959E+02 DEG.K   RE = 2.562E+07 1/M   THM = 4.153E-02 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8753	.2045	4.8890	0.0000
2	.0305	.8859	--	--	--	--
3	.0813	1.0380	.9040	.2407	4.1543	.4418
4	.1118	1.3021	.9160	.2617	3.8210	.5316
5	.1956	1.5331	.9157	.2874	3.4791	.5972
6	.2743	1.7165	.9168	.3104	3.2221	.6435
7	.5410	2.0293	.9284	.3516	2.8438	.7147
8	.7899	2.2988	.9401	.3917	2.5528	.7671
9	1.0846	2.6250	.9551	.4458	2.2432	.8211
10	1.5011	3.0853	.9712	.5353	1.8683	.8807
11	1.9834	3.5429	.9828	.6394	1.5640	.9252
12	2.4460	3.9449	.9900	.7437	1.3447	.9554
13	3.4417	4.4473	.9959	.8909	1.1724	.9840
* 14	4.7346	4.7119	.9992	.9748	1.0259	.9967
15	6.1189	4.7688	.9991	.9942	1.0058	.9988
** 16	7.3889	4.7883	1.0000	1.0000	1.0000	1.0000
17	6.2779	4.8222	1.0006	1.0111	.9890	1.0015
18	8.9383	4.8449	.9992	1.0203	.9801	1.0017

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108051   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 1.702E+00	ME = 4.788E+00	DEL = 4.735E+00 CM
PO = 1.030E+06 N/M2	DE = 1.382E-01 KG/M3	DSTR = 1.746E+00 CM
TO = 3.374E+02 DEG.K	TE = 6.041E+01 DEG.K	TH = 1.786E-01 CM
PSW = 2.363E+03 N/M2	UE = 7.461E+02 M/S	THE = 3.256E-01 CM
TW = 2.951E+02 DEG.K	RE = 2.571E+07 1/M	THM = 5.000E-02 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8746	.2047	4.8850	0.0000
2	.0305	.8859	.9060	.2286	4.3743	.3869
3	.0813	1.0388	.9069	.2399	4.1676	.4425
4	.1118	1.3021	.9127	.2627	3.8069	.5306
5	.1956	1.5331	.9125	.2884	3.4669	.5961
6	.2743	1.7165	.9178	.3100	3.2257	.6438
7	.5418	2.0293	.9295	.3512	2.8470	.7151
8	.7899	2.2989	.9372	.3929	2.5451	.7659
9	1.0846	2.6250	.9479	.4492	2.2264	.8180
10	1.5011	3.0853	.9620	.5404	1.8504	.8765
11	1.9634	3.5425	.9741	.6451	1.5502	.9211
12	2.4460	3.9449	.9847	.7477	1.3374	.9528
13	3.4417	4.4473	.9954	.8914	1.1219	.9838
• 14	4.7346	4.7119	.9999	.9741	1.0265	.9970
15	6.1189	4.7688	.9998	.9935	1.0066	.9992
•• 16	7.3889	4.7883	1.0000	1.0000	1.0000	1.0000
17	8.2779	4.8222	1.0007	1.0110	.9892	1.0016
18	8.9383	4.8449	1.0005	1.0191	.9813	1.0023

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108052   CONICAL EQUILIBRIUM TEMPERATURE PROBE

```
STA = 1.702E+00        MF = 4.831E+00        DEL = 5.646E+00 CM
 PO = 5.164E+05 N/M2    DF = 6.974E-02 KG/M3  DSTR = 2.055E+00 CM
 TO = 3.380E+02 DEG.K   TE = 5.966E+01 DEG.K   TH = 2.009E-01 CM
PSW = 1.195E+03 N/M2    UE = 7.479E+02 M/S    THE = 3.652E-01 CM
 TW = 2.954E+02 DEG.K   RE = 1.320E+07 1/M    THH = 4.890E-02 CM
```

N	Y(CM)	M	TT/TTE	O/DE	T/TE	U/UE
1	0.0000	0.0000	.8737	.2020	4.9511	0.0000
2	.0305	.6208	--	--	--	--
3	.0483	.9123	--	--	--	--
4	.0991	1.2813	.9210	.2545	3.9290	.5258
5	.2134	1.4548	.9212	.2727	3.6676	.5768
6	.3277	1.6739	.9245	.2979	3.3572	.6349
7	.7214	2.0612	.9313	.3505	2.8530	.7207
8	1.2802	2.5874	.9544	.4325	2.3122	.8145
9	1.9406	3.2204	.9724	.5578	1.7929	.8927
10	2.5425	3.7651	.9849	.6872	1.4552	.9403
11	3.1877	4.1691	.9907	.7973	1.2542	.5666
12	3.6957	4.4125	.9956	.8674	1.1528	.9808
13	4.4425	4.5954	.9969	.9246	1.0815	.9893
14	5.1105	4.6957	.9949	.9554	1.0463	.9943
• 15	5.6464	4.7456	.9975	.9737	1.0270	.9956
16	6.4872	4.7687	.9979	.9812	1.0192	.9966
17	7.6840	4.7934	.9943	.9890	1.0111	.9978
•• 18	8.8773	4.8305	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108052   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 1.702E+00   ME = 4.831E+00   DEL = 5.646E+00 CM
PO = 5.164E+05 N/M2   DE = 6.956E-02 KG/M3   DSTA = 2.053E+00 CM
TO = 3.389E+02 DEG.K   TE = 5.981E+01 DEG.K   TH = 2.022E-01 CM
PSW = 1.195E+03 N/M2   UE = 7.489E+02 M/S   THE = 3.673E-01 CM
TW = 2.960E+02 DEG.K   RE = 1.314E+07 1/M   THH = 5.138E-02 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8734	.2020	4.9493	0.0000
2	.0305	.6208	.8965	.2120	4.7166	.2791
3	.0483	.9123	.9105	.2261	4.4235	.3972
4	.0991	1.2813	.9160	.2559	3.9078	.5243
5	.2134	1.4547	.9147	.2746	3.6417	.5747
6	.3277	1.6739	.9199	.2993	3.3406	.6334
7	.7214	2.0612	.9300	.3510	2.8492	.7203
8	1.2802	2.5874	.9508	.4341	2.3035	.8130
9	1.9406	3.2204	.9700	.5593	1.7880	.8915
10	2.5425	3.7650	.9806	.6901	1.4490	.9382
11	3.1877	4.1692	.9919	.7964	1.2556	.9671
12	3.6957	4.4125	.9962	.8670	1.1534	.9811
13	4.4425	4.5954	.9982	.9235	1.0829	.9900
14	5.1105	4.6957	.9983	.9563	1.0456	.9940
• 15	5.6464	4.7457	.9979	.9734	1.0273	.9958
16	6.4372	4.7688	.9988	.9803	1.0201	.9971
17	7.6860	4.7934	.9995	.9879	1.0123	.9984
•• 18	8.8773	4.8305	1.0000	1.0000	1.0000	1.0000

8-4

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108053   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 1.702E+00	ME = 4.785E+00	DEL = 7.175E+00 CM
PO = 1.004E+05 N/M2	DE = 1.446E-02 KG/M3	DSTH = 2.567E+00 CM
TO = 3.342E+02 DEG.K	TE = 6.061E+01 DEG.K	TH = 2.567E-01 CM
PSJ = 2.441E+02 N/M2	UE = 7.468E+02 M/S	THE = 4.624E-01 CM
TW = 2.982E+02 DEG.K	RE = 2.684E+06 1/M	THM = 6.667E-02 CM

N	Y(CM)	M	TT/TTE	U/UE	T/TE	U/UF
1	0.0000	0.0000	.8818	.2032	4.9204	0.0000
2	.0305	.4959	--	--	--	--
3	.0457	.5115	--	--	--	--
4	.1321	.9289	.9175	.2290	4.3661	.4056
5	.2449	1.3549	.9402	.2610	3.8312	.5558
6	.3610	1.5464	.9468	.2852	3.5067	.6208
7	.5309	1.7288	.9469	.3031	3.2998	.6543
8	.6883	1.8851	.9456	.3242	3.0844	.6918
9	1.0719	2.1227	.9424	.3616	2.7657	.7377
10	1.6002	2.5150	.9562	.4245	2.3555	.8046
11	2.0930	2.8874	.9656	.4953	2.0194	.8675
12	2.6848	3.3300	.9743	.5919	1.6894	.9065
13	3.1928	3.6908	.9803	.6809	1.4686	.9347
14	3.8532	4.0475	.9883	.7903	1.2653	.9632
15	4.3536	4.3039	.9905	.8513	1.1747	.9768
16	5.0775	4.4991	.9930	.9112	1.0975	.9850
17	6.1545	4.6746	.9960	.9661	1.0330	.9934
* 18	7.1755	4.7329	.9984	.9837	1.0165	.9972
19	8.1382	4.7542	.9940	.9904	1.0097	.9983
** 20	9.0444	4.7852	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108053   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 1.702E+00	ME = 4.785E+00	DEL = 7.175E+00 CM
PO = 1.004E+05 N/M2	DE = 1.441E-02 KG/M3	DSTR = 2.561E+00 CM
TO = 3.396E+02 DEG.K	TE = 6.046E+01 DEG.K	TH = 2.689E-01 CM
PSW = 2.441E+02 N/M2	UE = 7.483E+02 M/S	THE = 4.727E-01 CM
TW = 2.976E+02 DEG.K	RE = 2.666E+06 1/M	THM = 7.070E-02 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8763	.2845	4.8893	0.0000
2	.0305	.4959	.8890	.2115	4.7279	.2253
3	.0457	.5115	.8932	.2111	4.7360	.2326
4	.1321	.9288	.9147	.2297	4.3527	.4050
5	.2489	1.3588	.9261	.2650	3.7739	.5516
6	.3810	1.5864	.9319	.2891	3.4588	.6166
7	.5309	1.7287	.9299	.3079	3.2475	.6510
8	.6883	1.8851	.9284	.3002	3.0280	.6855
9	1.0719	2.1227	.9323	.3655	2.7361	.7338
10	1.6802	2.5149	.9426	.4386	2.3221	.8009
11	2.0930	2.8874	.9569	.4996	2.0015	.8537
12	2.6848	3.3300	.9678	.5959	1.6783	.9015
13	3.1928	3.6909	.9750	.6846	1.4606	.9322
14	3.8532	4.0975	.9836	.7941	1.2594	.9609
15	4.3536	4.3039	.9898	.8519	1.1739	.9745
16	5.0775	4.4991	.9940	.9103	1.0986	.9855
17	6.1595	4.6796	.9977	.9664	1.0347	.9948
• 18	7.1755	4.7329	.9979	.9843	1.0160	.9969
19	8.1382	4.7542	.9990	.9903	1.0097	.9986
•• 20	9.0449	4.7852	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108104   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 2.057E+00	ME = 4.907E+00		DEL = 5.654E+00 CM		
PO = 5.171E+05 N/M2	UE = 6.836E-02 KG/M3		DSTR = 2.262E+00 CM		
TO = 3.38E+02 DEG.K	TE = 5.825E+01 DEG.K		TM = 2.047E-01 CM		
PSW = 1.132E+03 N/M2	UE = 7.508E+02 M/S		TMF = 3.715E-01 CM		
TW = 2.396E+02 DEG.K	RE = 1.335E+07 1/M		THM = 3.208E-02 CM		

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8844	.1944	5.1432	0.0000
2	.0305	.8131	--	--	--	--
3	.0508	1.0033	--	--	--	--
4	.0737	1.2272	--	--	--	--
5	.1018	1.3353	.9329	.2501	3.9492	.5442
6	.1245	1.4013	.9315	.2571	3.8496	.5632
7	.1524	1.4470	.9237	.2641	3.7866	.5738
8	.1829	1.4938	.9219	.2697	3.7073	.5861
9	.2164	1.5445	.9190	.2768	3.6124	.5998
10	.2616	1.5992	.9164	.2835	3.5277	.6117
11	.3435	1.7180	.9261	.2953	3.3869	.6443
12	.5664	1.8839	.9276	.3169	3.1553	.6820
13	.8382	2.1076	.9408	.3451	2.8974	.7311
14	1.0719	2.2881	.9528	.3694	2.7071	.7672
15	1.3259	2.5029	.9549	.4057	2.4651	.8008
16	1.5748	2.7128	.9687	.4388	2.2741	.8346
17	1.7755	2.8912	.9742	.4715	2.1207	.8580
18	2.0498	3.1300	.9746	.5194	1.9252	.8850
19	2.2708	3.3199	.9923	.5543	1.8009	.9079
20	2.5248	3.5503	.9876	.6130	1.6314	.9241
21	2.8499	3.8199	.9879	.6752	1.4811	.9474
22	3.0836	4.0267	.9922	.7353	1.3601	.9570
23	3.4672	4.4389	.9969	.8505	1.1758	.9809
24	4.5695	4.6256	1.0031	.9049	1.1050	.9909
25	5.1181	4.7447	.9999	.9462	1.0569	.9940
• 26	5.6541	4.8249	1.0027	.9699	1.0310	.9984
27	6.4110	4.8706	.9971	.9906	1.0095	.9973
28	6.9317	4.8817	.9996	.9919	1.0082	.9989
•• 29	7.6886	4.9071	1.0000	1.0000	1.0000	1.0000
30	8.2677	4.9161	.9973	1.0058	.9943	.9990
31	8.9156	4.9298	1.0018	1.0057	.9943	1.0017

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108104   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 2.057E+00   ME = 4.907E+00   DEL = 5.659E+00 CM
PO = 5.171E+05 N/M2   DE = 6.868E-02 KG/M3   DSTA = 2.253E+00 CM
TO = 3.372E+02 DEG.K   TE = 5.797E+01 DEG.K   TM = 2.138E-01 CM
PSW = 1.132E+03 N/M2   UE = 7.490E+02 M/S   TME = 3.884E-01 CM
TW = 2.979E+02 DEG.K   RE = 1.345E+07 1/M   TMM = 5.000E-02 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8836	.1946	5.1388	0.0000
2	.0305	.8131	.9128	.2133	4.6887	.3588
3	.0508	1.0033	.9149	.2258	4.4292	.4303
4	.0737	1.2272	.9203	.2431	4.1134	.5072
5	.1016	1.3353	.9171	.2543	3.9316	.5394
6	.1245	1.4013	.9172	.2611	3.8299	.5589
7	.1524	1.4470	.9159	.2663	3.7545	.5714
8	.1829	1.4938	.9155	.2716	3.6815	.5841
9	.2184	1.5485	.9219	.2760	3.6238	.6007
10	.2616	1.5982	.9241	.2811	3.5571	.6143
11	.3835	1.7180	.9269	.2950	3.3898	.6446
12	.5664	1.8839	.9252	.3178	3.1471	.6811
13	.8382	2.1076	.9398	.3455	2.8944	.7307
14	1.0719	2.2880	.9436	.3730	2.6809	.7634
15	1.3259	2.5029	.9560	.4052	2.4678	.8013
16	1.5748	2.7128	.9567	.4442	2.2510	.8294
17	1.7755	2.8912	.9684	.4744	2.1080	.8554
18	2.0498	3.1299	.9653	.5271	1.8971	.8785
19	2.2708	3.3200	.9751	.5650	1.7698	.9001
20	2.5248	3.5503	.9805	.6174	1.6196	.9207
21	2.8499	3.8200	.9841	.6846	1.4606	.9408
22	3.0836	4.0267	.9901	.7368	1.3571	.9560
23	3.9472	4.4389	.9934	.8552	1.1693	.9782
24	4.5695	4.6256	.9993	.9083	1.1009	.9891
25	5.1181	4.7448	.9982	.9478	1.0551	.9932
* 26	5.6591	4.8249	.9987	.9737	1.0270	.9964
27	6.4110	4.8706	.9977	.9901	1.0100	.9975
28	6.9317	4.8817	.9962	.9952	1.0049	.9972
** 29	7.6886	4.9071	1.0000	1.0000	1.0000	1.0000
30	8.2677	4.9161	.9976	1.0055	.9946	.9991
31	8.9154	4.9295	.9964	1.0112	.9889	.9990

NCL ROUNDARY LAYEH CHANNFL PROFILE DATA

RUN NO. 108105   CONICAL FQUILTRRIUM TEMPERATURE PRCBE

STA = 2.057E+00	ME = 4.756E+00	DFL = 6.411F+00 CM
PO = 1.024E+05 N/M2	DE = 1.409E-02 KG/M3	OSTR = 2.856F+00 CM
TO = 3.390E+02 DEG.K	TE = 6.137E+01 DEG.K	TH = 2.674E-01 CM
PSW = 2.467E+02 N/M2	UE = 7.469E+02 M/S	THE = 4.812E-01 CM
TW = 3.023E+02 DEG.K	HE = 2.577E+06 1/M	THH = 4.444E-02 CM

N	Y(CM)	M	IT/ITE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8919	.2030	4.9263	0.0000
2	.0305	.3721	--	--	--	--
3	.0559	.4481	-	--	--	--
4	.0838	.6077	.9156	.2124	4.7092	.2773
5	.1168	.7920	.9219	.2210	4.5242	.3542
6	.1600	.9830	.9289	.2326	4.3000	.4286
7	.2108	1.1764	.9367	.2468	4.0512	.4981
8	.2819	1.3616	.9524	.2606	3.8375	.5609
9	.6223	1.6999	.9501	.3007	3.3257	.6518
10	.9271	1.9235	.9472	.3326	3.0069	.7014
11	1.2497	2.1075	.9482	.3605	2.7736	.7389
12	1.5850	2.3095	.9524	.3929	2.5452	.7749
13	1.9279	2.5126	.9665	.4238	2.3594	.8115
14	2.3190	2.7863	.9739	.4746	2.1072	.8505
15	2.7940	3.0739	.9815	.5330	1.8761	.8853
16	3.1953	3.3441	.9867	.5939	1.6539	.9125
17	4.0107	3.8511	.9932	.7230	1.3831	.9523
18	4.4856	4.1281	.9949	.8022	1.2466	.9692
19	4.9657	4.3428	.9962	.8673	1.1530	.9806
20	5.6439	4.5206	.9982	.9260	1.0709	.9900
* 21	6.6110	4.6636	.9997	.9689	1.0 :	.9962
22	6.9037	4.7229	.9998	.9889	1.0 2	.9986
** 23	7.6987	4.7557	1.0000	1.0000	1. 0	1.0000
24	8.2042	4.7678	.9997	1.0044	54	1.0003
25	8.9078	4.7737	.9997	1.0065	35	1.0005

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108105   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 2.057E+00   ME = 4.756E+00   DEL = 6.411E+00 CM
PO = 1.034E+05 N/M2   DE = 1.407E-02 KG/M3   DSTR = 2.852E+00 CM
TO = 3.394E+02 DEG.K   TE = 6.145E+01 DEG.K   TH = 2.722E-01 CM
PSW = 2.467E+02 N/M2   UE = 7.473E+02 M/S   THE = 4.895E-01 CM
TW = 3.023E+02 DEG.K   RE = 2.571E+06 1/M   THH = 5.399E-02 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.8908	.2032	4.9203	0.0000
2	.0305	.3720	.9019	.2063	4.8472	.1722
3	.0559	.4480	.9100	.2069	4.8324	.2071
4	.0838	.6077	.9100	.2136	4.6507	.2765
5	.1168	.7920	.9270	.2198	4.5496	.3552
6	.1600	.9830	.9302	.2322	4.3059	.4289
7	.2108	1.1769	.9331	.2478	4.0359	.4972
8	.2819	1.3616	.9352	.2654	3.7683	.5558
9	.6223	1.6999	.9424	.3031	3.2992	.6492
10	.9271	1.9235	.9417	.3345	2.9894	.6993
11	1.2497	2.1074	.9436	.3623	2.7601	.7362
12	1.5850	2.3095	.9479	.3947	2.5333	.7730
13	1.9279	2.5125	.9555	.4287	2.3327	.8069
14	2.3190	2.7862	.9682	.4773	2.0950	.8480
15	2.7940	3.0739	.9754	.5364	1.8643	.8825
16	3.1953	3.3441	.9812	.5972	1.6744	.9099
17	4.0107	3.8511	.9904	.7251	1.3792	.9510
18	4.4856	4.1281	.9929	.8039	1.2440	.9682
19	4.9657	4.3427	.9958	.8676	1.1526	.9804
20	5.6439	4.5305	.9982	.9259	1.0800	.9900
• 21	6.4110	4.6635	1.0010	.9676	1.0335	.9969
22	6.9037	4.7229	1.0000	.9883	1.0114	.9987
•• 23	7.6987	4.7557	1.0000	1.0000	1.0000	1.0000
24	8.2042	4.7678	1.0009	1.0032	.9968	1.0009
25	8.9078	4.7737	.9995	1.0067	.9934	1.0005

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108091   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 1.702E+00	ME = 4.914E+00	DEL = 6.510E+00 CM
PO = 1.031E+06 N/M2	DF = 1.101E-01 KG/M3	DSTR = 1.814E+00 CM
TO = 4.255E+02 DEG.K	TE = 7.299E+01 DEG.K	TH = 2.419E-01 CM
PSW = 2.296E+03 N/M2	UF = 8.416E+02 M/S	THE = 4.455E-01 CM
TW = 3.030E+02 DEG.K	RE = 1.867E+07 1/M	THH = 1.596E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7121	.2409	4.1511	0.0000
2	.0305	1.1854	--	--	--	--
3	.0533	1.3890	--	--	--	--
4	.1118	1.5790	.8201	.3135	3.1898	.5739
5	.1981	1.7307	.8271	.3316	3.0152	.6116
6	.2794	1.8321	.8345	.3446	2.9022	.6374
7	.3937	1.9906	.8454	.3637	2.7493	.6717
8	.5664	2.1868	.8588	.3908	2.5589	.7119
9	.8179	2.4543	.8767	.4314	2.3180	.7604
10	1.0719	2.7288	.8945	.4774	2.0946	.8037
11	1.3437	3.0201	.9116	.5315	1.8315	.8430
12	1.6485	3.3342	.9273	.5963	1.6769	.8787
13	2.0422	3.7019	.9438	.6799	1.4707	.9136
14	2.3927	3.9890	.9530	.7529	1.3283	.9356
15	2.8346	4.2314	.9620	.8169	1.2241	.9527
16	3.5662	4.4896	.9725	.8875	1.1268	.9696
17	4.4450	4.6987	.9820	.9461	1.0570	.9831
18	5.1410	4.7706	.9890	.9630	1.0384	.9893
19	5.8801	4.8130	.9925	.9736	1.0271	.9927
* 20	6.5100	4.8399	.9962	.9790	1.0215	.9955
21	7.6048	4.8645	.9983	.9851	1.0151	.9974
** 22	8.9078	4.9139	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108091   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 1.702E+00	ME = 4.914E+00	DEL = 6.510E+00 CM
PO = 1.031E+06 N/M2	DE = 1.098E-01 KG/M3	DSTR = 1.813E+00 CM
TO = 4.266E+02 DEG.K	TE = 7.319E+01 DEG.K	TH = 2.428E-01 CM
PSW = 2.296E+03 N/M2	UE = 8.427E+02 M/S	THE = 4.470E-01 CM
TW = 3.039E+02 DEG.K	RE = 1.859E+07 1/M	THH = 1.613E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7123	.2408	4.1522	
2	.0305	1.1854	.8065	.2725	3.6698	0.0000
3	.0533	1.3891	.8161	.2913	3.4328	.4621
4	.1118	1.5790	.8231	.3124	3.2015	.5237
5	.1981	1.7307	.8328	.3294	3.0359	.5750
6	.2794	1.8386	.8403	.3422	2.9225	.6137
7	.3937	1.9906	.8494	.3620	2.7624	.6396
8	.5664	2.1868	.8606	.3900	2.5642	.6733
9	.8179	2.4543	.8759	.4318	2.3160	.7126
10	1.0719	2.7288	.8914	.4790	2.0875	.7601
11	1.3437	3.0201	.9051	.5353	1.8681	.8023
12	1.6485	3.3343	.9210	.6004	1.6656	.8400
13	2.0422	3.7028	.9361	.6855	1.4587	.8757
14	2.3927	3.9891	.9483	.7566	1.3217	.9099
15	2.8346	4.2315	.9601	.8185	1.2217	.9333
16	3.5662	4.4896	.9722	.8877	1.1265	.9518
17	4.4450	4.6987	.9840	.9441	1.0592	.9697
18	5.1410	4.7706	.9905	.9635	1.0400	.9841
19	5.8801	4.8130	.9951	.9711	1.0298	.9901
* 20	6.5100	4.8399	.9961	.9791	1.0214	.9939
21	7.6048	4.8645	.9969	.9865	1.0137	.9954
** 22	8.9078	4.9140	1.0000	1.0000	1.0000	.9967
						1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 10R054   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 1.702E+00	ME = 4.875E+00	DEL = 6.883E+00 CM
PO = 5.178E+05 N/M2	DE = 5.40RE-02 KG/M3	DSTR = 1.958E+00 CM
TO = 4.230E+02 DEG.K	TE = 7.352E+01 DEG.K	TH = 2.723E-01 CM
PSW = 1.135E+03 N/M2	UE = 8.380E+02 M/S	THE = 4.981E-01 CM
TW = 3.004E+02 DEG.K	RE = 9.064E+06 1/M	TMH = 1.916E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7102	.2447	4.0863	0.0000
2	.0305	.8178	--	--	--	--
3	.0356	.4670	--	--	--	--
4	.0533	1.1747	--	--	--	--
5	.0914	1.3976	.8073	.2994	3.3401	.5239
6	.1372	1.5270	.8169	.3112	3.2133	.5615
7	.2184	1.6550	.8233	.3267	3.0606	.5938
8	.2946	1.7411	.8266	.3378	2.9605	.6144
9	.4318	1.8946	.8357	.3573	2.7940	.6501
10	.5766	2.0406	.8442	.3773	2.6503	.6814
11	.7315	2.1901	.8546	.3965	2.5097	.7116
12	.8915	2.3426	.8645	.4217	2.3716	.7399
13	1.0871	2.5365	.8763	.4535	2.2050	.7725
14	1.2675	2.7152	.8872	.4847	2.0631	.7999
15	1.4707	2.9107	.8983	.5213	1.9184	.8269
16	1.6967	3.1284	.9097	.5650	1.7699	.8536
17	1.8339	3.2531	.9144	.5923	1.6682	.8670
18	2.0879	3.4781	.9274	.6408	1.5605	.8912
19	2.3547	3.7155	.9367	.6978	1.4332	.9123
20	2.7026	3.9672	.9456	.7623	1.3116	.9320
21	3.1801	4.2499	.9562	.8383	1.1929	.9521
22	3.9624	4.5291	.9697	.9145	1.0934	.9714
23	4.4704	4.6328	.9762	.9423	1.0613	.9789
24	5.1308	4.7307	.9840	.9671	1.0360	.9867
25	5.7531	4.7802	.9888	.9790	1.0214	.9909
26	6.3957	4.8109	.9938	.9863	1.0159	.9946
• 27	6.8836	4.8335	.9961	.9897	1.0104	.9966
•• 28	8.1382	4.8754	1.0000	1.0000	1.0000	1.0000
29	9.1745	4.9174	1.0033	1.0110	.9892	1.0031

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108054   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 1.702E+00   ME = 4.875E+00   DEL = 6.883E+00 CM
 PO = 5.178E+05 N/M2   DE = 5.435E-02 KG/M3   DSTR = 1.961E+00 CM
 TO = 4.209E+02 DEG.K   TE = 7.315E+01 DEG.K   TH = 2.697E-01 CM
PSW = 1.135E+03 N/M2   UE = 8.359E+02 M/S   THE = 4.936E-01 CM
 TW = 3.000E+02 DEG.K   RE = 9.137E+06 1/M   THM = 1.866E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7128	.2438	4.1017	0.0000
2	.0305	.8178	.7830	.2516	3.9739	.3344
3	.0356	.9670	.7932	.2601	3.8450	.3889
4	.0533	1.1797	.8071	.2753	3.6327	.4612
5	.0914	1.3976	.8172	.2957	3.3814	.5271
6	.1372	1.5270	.8221	.3100	3.2257	.5625
7	.2184	1.6550	.8276	.3250	3.0767	.5954
8	.2946	1.7411	.8334	.3349	2.9856	.6170
9	.4318	1.8946	.8424	.3544	2.8216	.6527
10	.5766	2.0406	.8518	.3739	2.6743	.6844
11	.7315	2.1901	.8608	.3956	2.5281	.7142
12	.8915	2.3426	.8703	.4189	2.3874	.7424
13	1.0871	2.5365	.8807	.4513	2.2159	.7745
14	1.2675	2.7152	.8903	.4831	2.0702	.8013
15	1.4707	2.9107	.8982	.5214	1.9180	.8268
16	1.6967	3.1283	.9104	.5645	1.7715	.8540
17	1.8339	3.2531	.9157	.5915	1.6906	.8676
18	2.0879	3.4780	.9249	.6425	1.5565	.8900
19	2.3597	3.7155	.9345	.6994	1.4298	.9112
20	2.9026	3.9672	.9463	.7617	1.3128	.9323
21	3.1801	4.2499	.9588	.8360	1.1962	.9534
22	3.9624	4.5202	.9698	.9144	1.0936	.9715
23	4.4704	4.6328	.9769	.9416	1.0620	.9793
24	5.1308	4.7307	.9852	.9660	1.0352	.9872
25	5.7534	4.7801	.9901	.9777	1.0228	.9916
26	6.3957	4.8109	.9933	.9849	1.0154	.9943
• 27	6.8807	4.8335	.9959	.9898	1.0103	.9965
•• 28	8.1382	4.8755	1.0000	1.0000	1.0000	1.0000
29	9.1745	4.9174	1.0000	1.0143	.9859	1.0015

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 10H055   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 1.702E+00   ME = 4.787E+00   DEL = 8.164E+00 CM
 PO = 1.013E+05 N/M2   OE = 1.136E-02 KG/M3 DSTR = 2.442E+00 CM
 TO = 4.210E+02 DEG.K   TE = 7.540E+01 DEG.K   TH = 4.049E-01 CM
PSW = 2.432E+02 N/M2   UE = 8.333E+02 M/S   THF = 7.353E-01 CM
 YW = 2.990E+02 DEG.K   WF = 1.842E+06 1/M   THM = 3.520E-01 CM

N	Y(CM)	M	TT/TTE	O/OE	T/TE	U/UE
1	0.0000	0.0000	.7102	.2522	3.9651	0.0000
2	.0305	.3857	--	--	--	--
3	.0356	.4298	--	--	--	--
4	.0834	.6922	.7443	.2630	3.8024	.2820
5	.1067	.8581	.7579	.2711	3.6886	.3443
6	.1321	.9908	.7702	.2782	3.5945	.3924
7	.1600	1.1155	.7828	.2857	3.4999	.4359
8	.1981	1.2748	.7964	.2960	3.3559	.4878
9	.2540	1.4299	.8087	.3120	3.2047	.5347
10	.6096	1.8124	.8235	.3604	2.7749	.6307
11	.7747	1.9743	.8277	.3850	2.5971	.6646
12	1.0312	2.1632	.8340	.4158	2.4052	.7008
13	2.0650	2.9168	.8675	.5577	1.7929	.8159
14	2.3114	3.1012	.8753	.5982	1.6716	.8376
15	2.5603	3.2818	.8834	.6395	1.5638	.8573
16	3.1801	3.6907	.9018	.7394	1.3520	.8964
17	3.8379	4.0565	.9187	.8365	1.1954	.9265
18	4.4628	4.3010	.9331	.9021	1.1086	.9459
19	5.1384	4.5007	.9493	.9530	1.0443	.9631
20	5.7302	4.6035	.9608	.9765	1.0241	.9731
21	6.2662	4.6595	.9700	.9865	1.0137	.9800
22	6.9164	4.7085	.9804	.9927	1.0073	.9872
23	7.5108	4.7327	.9888	.9925	1.0075	.9923
* 24	8.1636	4.7660	.9946	.9982	1.0018	.9965
** 25	9.0449	4.7871	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108055   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 1.702E+00   ME = 4.787E+00   DEL = 8.164E+00 CM
 PO = 1.013E+05 N/M2   DE = 1.136E-02 KG/M3   DSTR = 2.442E+00 CM
 TO = 4.211E+02 DEG.K   TE = 7.542E+01 DEG.K   TH = 4.014E-01 CM
PSW = 2.432E+02 N/M2   UE = 8.334E+02 M/S   TME = 7.275E-01 CM
 TW = 2.992E+02 DEG.K   RE = 1.841E+06 1/M   THM = 3.462E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7106	.2520	3.9676	0.0000
2	.0305	.3857	.7420	.2486	4.0233	.1616
3	.0356	.4298	.7446	.2494	4.0091	.1798
4	.0838	.6921	.7652	.2565	3.8988	.2455
5	.1067	.8581	.7758	.2649	3.7757	.3483
6	.1321	.9908	.7847	.2731	3.6622	.3961
7	.1600	1.1155	.7902	.2831	3.5328	.4380
8	.1981	1.2748	.7994	.2969	3.3686	.4888
9	.2540	1.4299	.8055	.3133	3.1922	.5337
10	.6096	1.8124	.8181	.3627	2.7569	.6286
11	.7747	1.9743	.8226	.3874	2.5811	.6626
12	1.0312	2.1632	.8287	.4183	2.3905	.6987
13	2.0650	2.9168	.8635	.5604	1.7845	.8139
14	2.3114	3.1012	.8727	.6000	1.6667	.8363
15	2.5603	3.2819	.8811	.6412	1.5596	.8562
16	3.1801	3.6907	.9002	.7409	1.3497	.8957
17	3.8379	4.0565	.9116	.8366	1.1953	.9264
18	4.4428	4.3009	.9341	.9011	1.1098	.9465
19	5.1384	4.5007	.9518	.9505	1.0521	.9643
20	5.7302	4.6035	.9638	.9735	1.0273	.9747
21	6.2662	4.6595	.9739	.9824	1.0179	.9820
22	6.9164	4.7086	.9839	.9892	1.0109	.9889
23	7.5108	4.7328	.9904	.9909	1.0092	.9932
* 24	8.1636	4.7659	.9965	.9962	1.0038	.9975
** 25	9.0449	4.7872	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108101   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 2.057F+00   ME = 4.972F+00   DEL = 4.937F+00 CM
 PO = 1.032E+06 N/M2   DE = 1.109F-01 KG/M3   DSTR = 2.004E+00 CM
 TO = 6.235E+02 DEG.K   TF = 7.126F+01 DEG.K   TH = 2.607F-01 CM
PSW = 2.245E+03 N/M2   UF = 8.413E+02 M/S   TME = 4.784E-01 CM
 TW = 3.034E+02 DEG.K   MF = 1.931F+07 1/M   THM = 1.725F-01 CM

N	Y(CM)	M	TT/TTF	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7164	.2348	4.2583	0.0000
2	.0305	1.0964	--	--	--	--
3	.0404	1.2163	--	--	--	--
4	.0544	1.3625	--	--	--	--
5	.0838	1.4978	.8109	.3006	3.3269	.5445
6	.1270	1.5946	.8184	.3101	3.2246	.5754
7	.1676	1.6645	.8232	.3176	3.1483	.5940
8	.2210	1.7323	.8274	.3254	3.0733	.6108
9	.2972	1.8341	.8339	.3375	2.9631	.6350
10	.4343	1.9927	.8446	.3574	2.7981	.6704
11	.7595	2.2946	.8634	.4001	2.4995	.7247
12	1.0643	2.5646	.8819	.4417	2.2639	.7761
13	1.4326	2.9078	.9038	.5009	1.9962	.8263
14	1.8263	3.2794	.9245	.5734	1.7439	.8710
15	2.1946	3.6063	.9345	.6449	1.5507	.9032
16	2.6264	3.9977	.9538	.7402	1.3510	.9366
17	3.2055	4.3082	.9631	.8232	1.2148	.9551
18	3.8583	4.5542	.9712	.8918	1.1213	.9700
19	4.4018	4.6961	.9785	.9303	1.0769	.9743
20	5.1283	4.8098	.9847	.9613	1.0402	.9867
21	5.7531	4.8638	.9897	.9742	1.0265	.9911
• 22	6.9367	4.9146	.9962	.9847	1.0155	.9961
23	7.6632	4.9471	.9979	.9939	1.0062	.9981
24	8.2017	4.9538	.9991	.9949	1.0051	.9989
•• 25	8.9433	4.9719	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108101   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 2.057E+00   ME = 4.972E+00   DEL = 6.937E+00 CM
 PO = 1.032E+06 N/M2   OE = 1.107E-01 KG/M3   OSTR = 2.002E+00 CM
 TO = 4.243E+02 DEG.K   TE = 7.139E+01 DEG.K   TH = 2.623E-01 CM
PSW = 2.246E+03 N/M2   UE = 5.421E+02 M/S   THE = 4.809E-01 CM
 TW = 3.042E+02 DEG.K   RE = 1.925E+07 1/M   THH = 1.754E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7170	.2347	4.2614	0.0000
2	.0305	1.0964	.8002	.2608	3.8344	.4318
3	.0406	1.2163	.8074	.2700	3.7034	.4708
4	.0584	1.3625	.8129	.2838	3.5232	.5144
5	.0838	1.4978	.8167	.2984	3.3510	.5515
6	.1270	1.5945	.8205	.3093	3.2328	.5767
7	.1676	1.6645	.8256	.3167	3.1577	.5949
8	.2210	1.7323	.8318	.3237	3.0897	.6125
9	.2972	1.8340	.8384	.3357	2.9790	.6367
10	.4343	1.9927	.8475	.3562	2.8076	.6716
11	.7595	2.2946	.8633	.4001	2.4592	.7296
12	1.0643	2.5645	.8770	.4442	2.2513	.7739
13	1.4326	2.9077	.8964	.5051	1.9799	.8229
14	1.8263	3.2794	.9141	.5799	1.7244	.8662
15	2.1946	3.6062	.9248	.6516	1.5348	.8986
16	2.6264	3.9976	.9482	.7446	1.3431	.9318
17	3.2055	4.3081	.9612	.8248	1.2125	.9541
18	3.8583	4.5542	.9715	.8915	1.1217	.9701
19	4.4018	4.6960	.9798	.9290	1.0764	.9799
20	5.1283	4.8097	.9879	.9582	1.0436	.9883
21	5.7531	4.8637	.9925	.9715	1.0293	.9925
* 22	6.9367	4.9145	.9965	.9844	1.0158	.9963
23	7.6632	4.9470	.9986	.9931	1.0069	.9985
24	8.2017	4.9537	.9967	.9972	1.0028	.9977
** 25	8.9433	4.9718	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108102   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 2.057E+00	ME = 4.866E+00	DEL = 7.036E+00 CM
PO = 5.171E+05 N/M2	DE = 5.508E-02 KG/M3	DSTR = 2.142E+00 CM
TO = 4.220E+02 DEG.K	TE = 7.363E+01 DEG.K	TH = 3.026E-01 CM
PSW = 1.156E+03 N/M2	UE = 8.366E+02 M/S	TMF = 5.507E-01 CM
TW = 3.020E+02 DEG.K	RE = 9.202E+06 1/M	THM = 2.175E-01 CM

N	Y(CM)	M	TT/TTE	U/DE	T/TE	U/UE
1	0.0000	0.0000	.7158	.2438	4.1021	0.0000
2	.0305	.8353	--	--	--	--
3	.0457	1.0475	--	--	--	--
4	.0584	1.1700	--	--	--	--
5	.0838	1.3494	.7965	.2988	3.3465	.5075
6	.1092	1.4388	.8095	.3048	3.2809	.5358
7	.1346	1.5026	.8138	.3112	3.2130	.5538
8	.1880	1.5818	.8158	.3212	3.1130	.5738
9	.2311	1.6372	.8160	.3284	3.0447	.5873
10	.2946	1.7079	.8190	.3374	2.9642	.6046
11	.4623	1.8705	.8292	.3577	2.7957	.6430
12	.6756	2.0552	.8382	.3840	2.6034	.6819
13	.9093	2.2450	.8519	.4113	2.4315	.7198
14	1.2014	2.4776	.8673	.4482	2.2312	.7609
15	1.4402	2.6754	.8803	.4819	2.0749	.7924
16	1.7043	2.9051	.8934	.5249	1.9050	.8266
17	1.9634	3.1270	.9042	.5697	1.7553	.8518
18	2.2631	3.3720	.9146	.6214	1.6093	.8795
19	2.5324	3.6034	.9265	.6759	1.4795	.9012
20	3.1953	4.0709	.9453	.7464	1.2557	.9374
21	3.8433	4.3783	.9578	.8804	1.1355	.9543
22	4.3561	4.5284	.9647	.9207	1.0861	.9703
23	5.1257	4.6803	.9778	.9602	1.0415	.9820
24	5.6515	4.7548	.9855	.9776	1.0229	.9887
25	6.3681	4.8129	.9921	.9906	1.0095	.9942
• 26	7.0358	4.8391	.9961	.9955	1.0045	.9972
27	7.6378	4.8528	.9982	.9981	1.0019	.9987
•• 28	8.1915	4.8637	1.0000	1.0000	1.0000	1.0000
29	8.9255	4.8742	1.0002	1.0033	.9967	1.0005

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108102   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 2.057E+00		ME = 4.864E+00		DEL = 7.036E+00	CM
PO = 5.171E+05 N/M2		DE = 5.521E-02 KG/M3		DSTR = 2.144E+00	CM
TO = 4.210E+02 DEG.K		TE = 7.346E+01 DEG.K		TH = 3.008E-01	CM
PSW = 1.156E+03 N/M2		UE = 8.357E+02 M/S		TME = 5.477E-01	CM
TW = 3.029E+02 DEG.K		RE = 9.236E+06 1/M		THM = 2.141E-01	CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7195	.2425	4.1238	0.0000
2	.0305	.8353	.7844	.2535	3.9448	.3411
3	.0457	1.0475	.7963	.2672	3.7426	.4167
4	.0584	1.1700	.8034	.2766	3.6147	.4573
5	.0838	1.3494	.8112	.2934	3.4079	.5122
6	.1092	1.4388	.8138	.3032	3.2986	.5373
7	.1346	1.5026	.8184	.3095	3.2313	.5554
8	.1880	1.5818	.8204	.3191	3.1338	.5757
9	.2311	1.6372	.8236	.3254	3.0729	.5901
10	.2946	1.7079	.8269	.3341	2.9929	.6075
11	.4623	1.8705	.8370	.3544	2.8220	.6461
12	.6756	2.0552	.8461	.3804	2.6286	.6851
13	.9093	2.2450	.8568	.4089	2.4454	.7218
14	1.2014	2.4776	.8708	.4464	2.2404	.7625
15	1.4402	2.6754	.8802	.4820	2.0747	.7923
16	1.7043	2.9051	.8932	.5251	1.9045	.8243
17	1.9634	3.1270	.9015	.5720	1.7482	.8501
18	2.2631	3.3719	.9148	.6245	1.6013	.8773
19	2.5324	3.6034	.9238	.6793	1.4720	.8989
20	3.1953	4.0709	.9450	.7966	1.2553	.9378
21	3.8633	4.3783	.9589	.8796	1.1369	.9598
22	4.3561	4.5283	.9683	.9192	1.0879	.9711
23	5.1257	4.6803	.9799	.9582	1.0437	.9831
24	5.6515	4.7548	.9867	.9764	1.0241	.9893
25	6.3881	4.8129	.9930	.9897	1.0104	.9947
• 26	7.0358	4.8391	.9953	.9963	1.0037	.9968
27	7.6378	4.8528	.9991	.9972	1.0028	.9991
•• 28	8.1915	4.8638	1.0000	1.0000	1.0000	1.0000
29	8.9256	4.8742	1.0011	1.0025	.9976	1.0009

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 10H103   CONICAL EQUILIBRIUM TEMPERATURE PROBE

STA = 2.057E+00   ME = 4.804E+00   UEL = 8.304E+00 CM
 PO = 1.013E+05 N/M2   DF = 1.155E-02 KG/M3   DSTH = 2.714E+00 CM
 TO = 4.187E+02 DEG.K   TE = 7.451E+01 DEG.K   TH = 6.395E-01 CM
PSW = 2.424E+02 N/M2   UF = 8.316E+02 M/S   THE = 7.940E-01 CM
 TW = 3.034E+02 DEG.K   ME = 1.494E+06 1/M   THH = 3.782E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7264	.2455	4.0737	0.0000
2	.0305	.4127	--	--	--	--
3	.0463	.4601	--	--	--	--
4	.0711	.5954	--	--	--	--
5	.1143	.8141	.7608	.2649	3.7752	.3241
6	.1651	1.0635	.7808	.2745	3.5784	.4186
7	.2104	1.2521	.7937	.2965	3.3957	.4801
8	.3460	1.5543	.8143	.3241	3.0853	.5681
9	.5994	1.7575	.8174	.3521	2.8399	.6161
10	.8690	1.9429	.8257	.3782	2.6438	.6573
11	1.1805	2.1248	.8291	.4084	2.4465	.6918
12	1.4630	2.3125	.8362	.4344	2.2757	.7260
13	1.8136	2.5208	.8506	.4751	2.1050	.7610
14	2.1819	2.7482	.8593	.5245	1.9067	.7943
15	2.5624	2.9973	.8709	.5714	1.7500	.8250
16	3.1902	3.4314	.8849	.6710	1.4903	.8717
17	3.8532	3.8516	.9074	.7779	1.2855	.9046
18	4.3467	4.1372	.9196	.8560	1.1663	.9305
19	5.1151	4.3963	.9350	.9253	1.0807	.9505
20	5.8776	4.5766	.9533	.9646	1.0324	.9676
21	6.7043	4.7039	.9720	.9433	1.0068	.9821
22	7.7851	4.7735	.9847	1.0022	.9978	.9921
* 23	8.3058	4.7904	.9944	1.0002	.9998	.9966
** 24	8.9256	4.8060	1.0000	1.0000	1.0000	1.0000

NOL BOUNDARY LAYER CHANNEL PROFILE DATA

RUN NO. 108103   COMBINED TEMPERATURE-PRESSURE PROBE

STA = 2.057E+00   ME = 4.806E+00   DEL = 8.306E+00 CM
 PO = 1.013E+05 N/M2 DE = 1.159E-02 KG/M3 DSTR = 2.725E+00 CM
 TO = 4.174E+02 DEG.K TE = 7.427E+01 DEG.K TH = 4.339E-01 CM
PSW = 2.428E+02 N/M2 UE = 8.302E+02 M/S   THE = 7.830E-01 CM
 TW = 3.036E+02 DEG.K RE = 1.903E+06 1/M   THH = 3.650E-01 CM

N	Y(CM)	M	TT/TTE	D/DE	T/TE	U/UE
1	0.0000	0.0000	.7275	.2446	4.0883	0.0000
2	.0305	.4107	.7430	.2476	4.0392	.1717
3	.0483	.4599	.7537	.2461	4.0638	.1929
4	.0711	.5953	.7656	.2489	4.0174	.2483
5	.1143	.8140	.7742	.2603	3.8414	.3320
6	.1651	1.0635	.7902	.2761	3.6216	.4211
7	.2108	1.2520	.8039	.2908	3.4393	.4831
8	.3480	1.5542	.8119	.3251	3.0763	.5672
9	.5994	1.7570	.8182	.3518	2.8428	.6164
10	.8890	1.9429	.8253	.3784	2.6426	.6572
11	1.1405	2.1247	.8282	.4089	2.4458	.6914
12	1.4630	2.3128	.8357	.4437	2.2698	.7249
13	1.9136	2.5208	.8482	.4764	2.0990	.7599
14	2.1819	2.7682	.8606	.5237	1.9096	.7959
15	2.5629	2.9972	.8708	.5715	1.7497	.8249
16	3.1902	3.4318	.8882	.6723	1.4875	.8709
17	3.8532	3.8515	.9067	.7786	1.2844	.9082
18	4.3967	4.1371	.9215	.8542	1.1707	.9314
19	5.1181	4.3942	.9383	.9220	1.0846	.9522
20	5.8776	4.5766	.9557	.9662	1.0350	.9668
21	6.7843	4.7037	.9754	.9897	1.0104	.9838
22	7.7851	4.7735	.9918	.9973	1.0027	.9946
• 23	8.3058	4.7904	.9955	.9992	1.0008	.9971
•• 24	8.9256	4.8060	1.0000	1.0000	1.0000	1.0000